

**PLEASE PRINT CLEARLY**

**ORDER QUANTITY** (minimum 1,000) \_\_\_\_\_

**LABEL INFORMATION** (to be printed on label)

Company Name: \_\_\_\_\_

Address: \_\_\_\_\_

Phone (Emergency Contact): \_\_\_\_\_

FEI PART NUMBER: LP-GHS-1-42-\_\_\_\_\_

LABEL SIZE: 3.25" x 15"

MINIMUM ORDER QUANTITY: 1,000

SETUP CHARGE: \$45.00 (first order only)

DEALER PRICE: \$0.58 per Label

PRINT LOGO ON LABEL:  Yes  No

LOGO FORMAT REQUIREMENTS:  
High Resolution (300 dpi) .eps or .pdf  
Available Logo Space: 2.5" x 2.1"



**FLAMMABLE GAS 2**

**LIQUEFIED PETROLEUM GAS**

**UN 1075**

**DANGER - FLAMMABLE GAS UNDER PRESSURE - LEAKING LP-GAS CAN CAUSE A FIRE OR EXPLOSION IF IGNITED-CONTACT LP-GAS SUPPLIER FOR REPAIRS OR DISPOSAL OF THIS CYLINDER OR UNUSED LP-GAS - FOR OUTDOOR USE ONLY - DO NOT USE OR STORE CYLINDER IN A BUILDING, GARAGE OR ENCLOSED AREA\***

Do not attempt repairs - Call your LP-Gas Dealer Turn off container valve when not in use.

- Extremely Flammable Gas
- Heavier Than Air
- Simple Asphyxiant
- Odorized to warn of its presence
- Contact with Liquid will cause Freezing of Tissue
- PEL 1000 PPM
- Store container outside and keep cool (under 130° F)

CONSULT CORRESPONDING SDS FOR FURTHER INFORMATION AND INSTRUCTIONS. AFFIX TO ALL PORTABLE CONTAINERS USED BY COMMERCIAL CUSTOMERS.

**PERSONAL PROTECTION**




**NFPA HAZARD RATING**

◆ FIRE HAZARD	4	4-Severe
◆ HEALTH HAZARD	2	3-Serious
◆ REACTIVITY	0	2-Moderate
		1-Slight
		0-Minimal






**YOUR COMPANY NAME & LOGO**

333 SOMESTREET • ANY PLACE, US 12345  
777-555-9999

Net Wt. \_\_\_\_\_ lbs. ( \_\_\_\_\_ Kgs)

DO NOT REMOVE, DEFACE OR OBLITERATE THIS LABEL  
\*EXCEPT AS AUTHORIZED BY NFPA 58

**FIG. 1 POL TYPE**



**FIG. 2 QCC TYPE**



**Customer Warning:**

- Know the odor of LP-gas. Under certain circumstances, you may not be able to smell the odorant. If you hear or smell leaking LP-gas, immediately get everyone away from the cylinder and call the fire department.
- Caution your LP-gas supplier to - purge the cylinder of trapped air prior to first filling. - check the cylinder requalification date - be certain not to overfill the cylinder.
- LP-gas is heavier than air and can settle in low places while discharging. - Contact with the liquid contents of the cylinder will cause freeze burns to the skin. - Do not allow children to tamper or play with the cylinder. - When the cylinder is not connected for use, keep the valve turned off. The valve should be capped.
- Do not use, store or transport cylinder where it could be exposed to high temperatures. Relief valve can open allowing a large amount of flammable gas to escape. - When transporting, keep cylinder secured in an upright position with cylinder valve turned off. - Self-contained outdoor cooking appliances must be limited to one cylinder of 20 lbs. LP-Gas capacity or less.

**When Connecting for Use:**

- Use only in compliance with applicable codes. - Read and follow appliance manufacturer's instructions. The cylinder contains an OPD (Overfill Prevention Device) equipped valve that can accept either a POL or QCC style coupling nut. If the appliance regulator has a male threaded coupling nut, it has left-handed threads and must be tightened by turning counter clockwise (Figure 1). If the regulator has a female threaded coupling nut, tightening the coupling nut by turning it clockwise (Figure 2). - Turn off all valves on appliance. - Do not check for gas leaks with a match or open flame. - Apply an approved leak detector solution at areas marked X in Figure 1 and Figure 2 and open valve. If bubbles appear, close valve and have an LP gas service person make needed repairs. Also, check appliance valves and connections for leakage before lighting appliance. - Light appliance(s) following manufacturer's instructions. - When appliance(s) is not in use, keep cylinder valve closed.

You may choose to return this Exchange Cylinder for a filled cylinder or have it re-filled by a propane retailer. Depending upon the date of its manufacture, this Exchange Cylinder may require requalification under United States Department of Transportation regulations before it can be re-filled. If you wish to avoid the cost of requalification, you can return this cylinder to any cylinder exchange location. No credit will be given on residual product. For more information about requalification, contact your local propane provider.

P/N:tbd (01/16)

**LABEL PROOF INFORMATION AND AUTHORIZATION**

Proof Approval Contact Person: \_\_\_\_\_

Phone: \_\_\_\_\_

Email: \_\_\_\_\_

A proof will be emailed to the contact person for review and approval signature before your order will be processed. Please return a copy of the SIGNED proof form within 48 hours of receipt. Approval signature indicates verification that you have checked the label proof for correct information and authorize the printing of labels as shown on the proof. Upon signature, you are responsible for taking possession of said labels. NO LABELS CAN BE RETURNED due to printing errors. FEI, Inc. and Label Solutions are not responsible for errors once approval signature has been received. Estimated lead time is 7-10 business days after authorization signature has been received.

Submit this completed form and your company logo in the format indicated above to: [custserv@feinc.com](mailto:custserv@feinc.com).

Your proof will be returned to the authorized contact person for review and approval as soon as it is available. No labels will be printed without authorized signature.